



7.10.1.2-4 Technical data and dimensions, 032 N3

TECHNICAL DATA

Pump: The pump is of positive displacement type
 Media: Fuel oil and lubricating oil
 Media temperature: Max 120°C
 Max feeding pressure: 0,3 MPa (3 bar)
 Material pump body: Nodular cast iron
 Material pump screw: Steel and cast iron
 Suction head: 4 m WG manometric
 0 m WG manometric for 2800 rpm and 3400 rpm
 Built on safety valve: Opening setting 0,6 MPa (6 bar)
 Motor: Totally enclosed three phase motor for marine applications
 Enclosure: IP55

Dimensions in mm

1762163-90	690	60	3400	565192-16	1,8	2,2	30	
1762163-89	690	60	1700	551590-18	1,3	1,9	30	
1762163-88	690	60	1100	551613-18	0,9	1,5	29,5	
1762163-87	690	50	2800	565192-07	1,5	1,9	30	
1762163-86	690	50	1400	551590-14	1,1	1,6	30	
1762163-85	690	50	900	551613-14	0,75	1,3	29,5	
1762163-84	575	60	1700	551590-06	1,3	2,2	30	
1762163-83	480	60	3400	565192-13	1,8	3,1	30	
1762163-82	480	60	1700	551590-08	1,3	2,8	30	
1762163-81	480	60	1100	551613-08	0,9	2,3	29,5	
1762163-80	460	60	3400	565192-12	1,8	3,2	30	
1762163-79	460	60	1700	551590-07	1,3	2,8	30	
1762163-78	460	60	1100	551613-07	0,9	2,3	29,5	
1762163-77	440	60	3400	565192-11	1,8	3,4	30	
1762163-76	440	60	1700	551590-05	1,3	2,9	30	
1762163-75	440	60	1100	551613-05	0,9	2,4	29,5	
1762163-74	400	50	2800	565192-02	1,5	3,2	30	
1762163-73	400	50	1400	551590-10	1,1	2,8	30	
1762163-72	400	50	900	551613-10	0,75	2,3	29,5	
1762163-71	230	60	3400	565192-18	1,8	6,5	30	
1762163-70	230	60	1700	551590-09	1,1	4,2	30	
1762163-69	230	60	1100	551613-09	0,75	3,5	29,5	
1762163-68	230	50	2800	565192-09	1,5	5,6	30	
1762163-67	230	50	1400	551590-11	1,1	4,9	30	
1762163-66	230	50	900	551613-11	0,75	4,0	29,5	
1762163-65	—	—	—	Pump without motor	—	—	17	
Article No.	Complete Set	Voltage	Hz	rpm	Motor(included)	Article No.	kW	Weight (kg)
							A	

Ref. 1762163 Rev. 5

